

FONTAINE RENEGADE™ LX LOWBED TRAILERS

FIND OUT WHY
MORE FLEETS
AND OWNER
OPERATORS
RUN WITH
FONTAINE® THAN
EVER BEFORE



Fontaine Renegade LX Lowbed

- MECHANICAL, REMOVABLE GOOSENECK WITH FIFTH WHEEL GUIDE ROLLERS
- TRUE 35 TON CAPACITY IN 16'¹
- 81° SWING RADIUS WITH 9' 10" OVERALL GOOSENECK LENGTH
- FLAT, LEVEL DECK WITH 29' 4" CLEAR DECK LENGTH
- FRONT OF DECK IS SLOPED AND FEATURES TRACTION CLEATS FOR EASIER LOADING AND UNLOADING
- AIR-RIDE SUSPENSION WITH AUTOMATIC AND MANUAL CONTROLS
- HIGHEST QUALITY 2-PART POLYURETHANE ENAMEL COATING FIGHTS CORROSION TO EXTEND TRAILER LIFE

ILoca Services, Inc.
Full Service Semi Trailer Dealer

Sales Service Parts Rentals Leasing

www.semitrailers.net

1-888-736-4826

RENEGADE™ LX LOWBED SPECIFICATIONS

MAIN BEAMS

- All main longitudinal members fabricated with 100 KSI minimum yield steel flanges with 50,000 lb webs

CAPACITY

- 35 tons in 16' length—GAWR and tire ratings determine legal payloads

LOAD BASE

- 16' rigid 2-point load centered in deck

DIMENSIONS

- Overall length: 48'
- Overall width: 8' 8"
- Clear deck length: 29' 4", flat level design
- Deck height under full load: 20" (ground clearance: 6")

LOADED FIFTH WHEEL HEIGHT

- Combination figure-eight plate provides 50" and 52" loaded height to easily accommodate a wide variety of trucks

SWING RADIUS

- 81" (9' 10" overall gooseneck length)

GOOSENECK DESIGN

- Mechanical removable with fifth wheel guide rollers

GOOSENECK PLATFORM

- Full-width gooseneck platform with 1 1/8" apitong floor for greater loading space
- Front deck length: 9' 10"

ELECTRICAL RECEPTACLE

- J560 7-pin connector

FRONT RAMP

- Front of deck is sloped and features traction cleats to make loading and unloading easier

FLOORING

- Full-width 1 3/8" nominal apitong

EXTENSION BRACKET MOUNTS

- 14 pair (28 total) to accommodate removable swing-type brackets
- 1 pair (2 total) to accommodate removable hook-on type brackets

BOGIE

- Fixed deck-to-bogie connection
- Full-width, sloped steel bogie ramp
- Covered rear bogie platform with 1 1/8" apitong floor
- Rear deck height: 39 1/2"
- Rear deck length: 8' 9"

AXLES

- 2 heavy-duty axles with 50" spread
- 25,000 lb nominal capacity per axle
- Tapered spindle axles, automatic slack adjusters and spring brakes
- 1 set of mudflaps

2S/2M ANTILOCK BRAKE SYSTEM

- ABS wired to center pin of 7-way socket at front
- Electronic sensors placed at every wheel end for greater braking control under various road conditions
- Virtually eliminates tire flat-spotting

BRAKES

- Spring brakes (2 axles)
- 16 1/2" x 7" with 5 1/2" autoslacks
- Heavy-duty brake drums, outboard mount
- Quick change replacement feature saves repair time
- Automatic slack adjusters maintain positive braking action

HUBS

- Hub-piloted 10-stud mount for increased capacity and durability
- Outboard cast drums save time and cost on brake repairs

WHEELS/TIRES

- 8.25 x 22.5 steel disc wheels with 255/70R 22.5 16-ply tires

SUSPENSION

- Smooth unitized air-ride suspension reduces driver fatigue and protects cargo
- Air-ride features automatic and manual controls
- Suspension mount is engineered, reinforced and braced to virtually eliminate frame cracking

ELECTRICAL SYSTEM

- Sealed harness for maximum corrosion resistance
- DOT sealed beam with LED lights
- 7 marker lights per side including mid-turn signal
- 3 stop, tail and turn lights per side on rear

PROTECTIVE COATING

- Best paint job in the industry—highest quality 2-part polyurethane enamel fights corrosion to extend the life of your trailer
- Shot blasted and cleaned prior to painting
- Primed for better paint adhesion

LASH RINGS

- 9 pair (18 total), bent lash rings provide chain clearance over siderail

FLAG HOLDERS

- 3 pair (6 total)

LIQUID FILLED GAUGE

- Standard

ACCENT PACKAGE

- Aluminum fenders at rear of gooseneck
- Stainless steel bumper insert
- Stainless steel laser-cut Renegade logo panel

FLIP AXLE CONNECTION

- Air/electrical connections in place for easy third axle connection

ESTIMATED EMPTY WEIGHT

W/O OPTIONS: 14,860 lbs ± 3%



Specifications subject to change without notice.
Photos show some optional equipment.

©2006 Fortaine Trailer • Get complete warranty details from your local Fortaine Dealer • LT-014 Mar 2006 7.5M

ILoca Services, Inc.
Full Service Semi Trailer Dealer

Sales Service Parts Rentals Leasing

www.semitrailers.net

1-888-736-4826