

TALBERT

Traveling Axle Trailers



6 DEGREE LOAD
ANGLE

28 DEGREE DUMP
ANGLE



35 TON & 50 TON CAPACITY



Triple reinforced approach plate lies flat with maximum ground bearing area to help protect pavement during loading and unloading of equipment (Standard)



Suspension straps are mounted on the shocks to prevent over extension of the air ride suspension (Standard)



Dock loading capabilities - 62,000 lbs. Levelers (Optional)

ALL SPECIFICATIONS AND STANDARD FEATURES

MODEL	8212150
CAPACITY	50,000 LBS DISTRIBUTED IN 40'-0" 50,000 LBS CONCENTRATED IN 30'-0"
FRAME	T3 & BOKEN BEAM CONSTRUCTION
LOAD ANGLE	4 DEGREE (20 DEGREE TO 30° ANGLE)
LENGTH	40'-0" OVERALL
LOADSPACE	19'-0" UPPER DECK, 30'-0" LOWER DECK
WHEELS	8'-0"
POWER SOURCE	12V OPERATOR
WINDING BARREL	30" (30" SETTING)
WINDING BARREL HT.	40" LOADED
FLOOR	1.587" APPLIED WITH SCREWS
WINCH	15,000 LBS. PLANETARY HYDRAULIC WITH AIR CLUTCH, 100'-0" 1/2" CABLE WITH TENSIONER ROLLER GUIDE, 30" ROLLER GUIDE IN LOWER DECK
REMOTE	DUAL REMOTE CONTROL
FOR WINCH	
LANDING GEAR	2 SPEED LANDING GEAR
TOOL BOX	LARGE LOCKABLE UNDER DOOR LOCK
CROSSMEMBERS	4" X 3" - BEAM ON 9" CENTERS (PORK LOFF PACKAGING)
TIE DOWNS	DOUBLE RIVET BOLT CHAIN SLOTS IN CENTER OF DECK & CHAIN HOLES ACROSS REAR APPROACH PLATE
DRY ICE BRAKES	30" LOADED 12 1/4" X 7 1/2" AIR WITH AUTO SLACK
ABS	26 IN SYSTEM
WHEELS	4.75 X 17.50 HOLE RIM PULLED WITH OIL WHEEL SEALS
TIRES	215/70R17.5 16PR RADIAL
SUSPENSION	8200WLL AIR
APPROACH PLATE	TRIPLE REINFORCED STEEL PLATE
REAR FLAPS	ANTI SLAG
LIGHTS	7 WAY PLUG WITH 5 LED LIGHTS
TRIM	CONDUCTIVITY TAPE
FINISH	STANDARD RED/GRANITE
WEIGHT	17,200 LBS (1-1/2%)

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

I/Loca Services, Inc.
Full Service Semi Trailer Dealer
www.semitrailers.net
1-800-736-4826



Cable roller in lower deck section for efficient loading with the winch (Standard)

Available Options

- 11'-0" LENGTH
- DOCK LEVELERS (62000 LBS.)
- HYDRAULIC LANDING GEAR
- 6000 PSI POWER PACKAGE
- FLIP UP RAMPS - UPPER DECK
- 2000 LBS. WINCH
- 4-WAY OR 10 FUNCTION REMOTE CONTROL
- 1/2" STEEL TREADPLATE (LOADING)
- BLIND COMPASS
- FLUSH MOUNTED "D" RINGS
- BLACK PAINT (STEEL OR ALUMINUM)
- 2 WING-OUT (OUTRIGGERS)
- ALUMINUM WHEELS
- 3 TAIL LIGHT PACKAGE
- ELECTRICAL PLUG AT REAR FOR BEACON
- MALE 4 WAY PLUG AT REAR
- ALUMINUM DRESS PACKAGE
- AIR WHEEL COUPLING SYSTEM
- 10" OR 1 1/2" METAL ON REAR OF DECK



Smooth transition from lower deck to upper deck for easier and safer loading (Standard) Heavy duty stainless steel hinges and latch, the most durable in the industry. (Standard)

Self-contained power package on a slide out tray provides easy access for service (Optional)

Visit us at our web site www.talbertmfg.com and try out our free to use weight distribution program for your truck and trailer



Planetary 15,000 lbs. hydraulic winch with air clutch, 100'-0" 1/2" cable w/ roller guide; tensioners & dual function wireless remote control for winch (Standard)

Two speed landing gear (Standard)

